

REFERENCE POWERED MONITORS

R-28PF



NO RECEIVER NEEDED

The Klipsch R-28PF internal amplifier eliminates the need for an expensive, complicated, external receiver.

REFERENCE ACOUSTICS

High Efficiency/Low Distortion, Wide Dynamic Range, Flat Frequency Response and Controlled Directivity are Klipsch's acoustic principles. These speakers embrace those ideals to deliver all the power, detail and emotion you would expect from a Klipsch Reference loudspeaker, no bullshit.

SIMPLE SETUP

With a wide range of digital, analog and wireless inputs, the R-28PF allows you to hook up any audio source quickly and easily.

OPTICAL DIGITAL AUDIO

Don't want a soundbar? Hook up your TV or other digital source with the included optical cable to enjoy big sound in your living room.

TURNTABLE READY

The built-in phono pre-amp lets you enjoy your favorite records without the need for additional electronics. Simply hook up your turntable and listen.

BLUETOOTH® WIRELESS TECHNOLOGY

Works great with all Bluetooth-enabled smartphones, tablets and computers allowing you to play music directly from your device.

HIGH EFFICIENCY AMPLIFICATION WITH DIGITAL CROSSOVER

The R-28PF floorstanding speakers incorporate bi-amplified ultra low-noise amplifiers custom-designed to maximize system performance. The digital equalizer and crossover allow our engineers to extract every ounce of performance without distortion.

SUBWOOFER OUTPUT WITH BASS MANAGEMENT

Want more bass? Use the subwoofer output to connect to any powered subwoofer. Enable the subwoofer output's bass management feature to perfectly blend your speaker with your subwoofer.

REMOTE CONTROL

An easy-to-use wireless remote control included.

EASY TO READ LED DISPLAY

LED array clearly shows the active input. Don't want to see the lights? Simply press the LED button on the remote to turn off the front facing LEDs

Klipsch®

REFERENCE



TURNTABLE READY



BLUETOOTH® WIRELESS TECHNOLOGY



TV READY



PC READY



NO RECEIVER NEEDED



SIMPLE SETUP

SPECIFICATIONS

SYSTEM DESCRIPTION	Powered Floorstanding Speakers (pair)
FREQUENCY RESPONSE	33Hz - 20kHz
MAX OUTPUT	114dB @ 1M
TOTAL SYSTEM POWER	260W Total System Power (520W Peak) Bi-Amplified Tweeter: 20W per channel cont. @ <1% THD+N Woofers: 110W per channel cont. @ <1% THD+N
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum diaphragm tweeter mated to 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 8" (10.2cm) copper spun magnetically shielded IMG woofer
CROSSOVER FREQUENCY	1700 Hz (active)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via front-firing port
INPUTS	<ul style="list-style-type: none"> • Bluetooth® wireless technology • Phono/Line analog (with switch and ground screw terminal) • 3.5mm analog mini jack • USB digital • Optical digital
OUTPUTS	Single RCA line level output for connection to subwoofer
HEIGHT, WIDTH, DEPTH	42" (106.6cm), 9.5" (24.1cm), 15.7" (39.8cm)
WEIGHT	56.67lbs (25.68kg)
FINISH	Brushed black polymer veneer
VOLTAGE	100V-120V / 220-240V selectable 50/60Hz internal power supply with region specific power cords
INCLUDED ACCESSORIES	<ul style="list-style-type: none"> • Remote control (with 2 x AAA batteries) • Magnetic grille • 5M speaker wire with 4-wire connector • 1.8M power cord (region specific) • 2M 3.5mm aux cable • 3M optical cable
BUILT FROM	2017

R28PF
UVP / Paar
1.299,00 €



REFERENCE POWERED MONITORS

R-26PF


Klipsch
REFERENCE


TURNTABLE READY

BLUETOOTH®
WIRELESS TECHNOLOGY

TV READY



PC READY



NO RECEIVER NEEDED



SIMPLE SETUP

NO RECEIVER NEEDED

The Klipsch R-26PF internal amplifier eliminates the need for an expensive, complicated, external receiver.

REFERENCE ACOUSTICS

High Efficiency/Low Distortion, Wide Dynamic Range, Flat Frequency Response and Controlled Directivity are Klipsch's acoustic principles. These speakers embrace those ideals to deliver all the power, detail and emotion you would expect from a Klipsch Reference loudspeaker, no bullshit.

SIMPLE SETUP

With a wide range of digital, analog and wireless inputs, the R-26PF allows you to hook up any audio source quickly and easily.

OPTICAL DIGITAL AUDIO

Don't want a soundbar? Hook up your TV or other digital source with the included optical cable to enjoy big sound in your living room.

TURNTABLE READY

The built-in phono pre-amp lets you enjoy your favorite records without the need for additional electronics. Simply hook up your turntable and listen.

BLUETOOTH® WIRELESS TECHNOLOGY

Works great with all Bluetooth-enabled smartphones, tablets and computers allowing you to play music directly from your device.

HIGH EFFICIENCY AMPLIFICATION WITH DIGITAL CROSSOVER

The R-26PF floorstanding speakers incorporate bi-amplified ultra low-noise amplifiers custom-designed to maximize system performance. The digital equalizer and crossover allow our engineers to extract every ounce of performance without distortion.

SUBWOOFER OUTPUT WITH BASS MANAGEMENT

Want more bass? Use the subwoofer output to connect any powered subwoofer. Enable the subwoofer output's bass management feature to perfectly blend your speaker with your subwoofer.

REMOTE CONTROL

An easy-to-use wireless remote control included.

EASY TO READ LED DISPLAY

LED array clearly shows the active input. Don't want to see the lights? Simply press the LED button on the remote to turn off the front facing LEDs.

SPECIFICATIONS

SYSTEM DESCRIPTION	Powered Floorstanding Speakers (pair)
FREQUENCY RESPONSE	38Hz - 20kHz
MAX OUTPUT	114dB @ 1M
TOTAL SYSTEM POWER	260W Total System Power (520W Peak) Bi-Amplified Tweeter: 20W per channel cont. @ <1% THD+N Woofers: 110W per channel cont. @ <1% THD+N
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum diaphragm tweeter mated to 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" (10.2cm) copper spun magnetically shielded IMG woofer
CROSSOVER FREQUENCY	1700 Hz (active/DSP)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via front-firing port
INPUTS	<ul style="list-style-type: none"> • Bluetooth® wireless technology • Phono/Line analog (with switch and ground screw terminal) • 3.5mm analog mini jack • USB digital • Optical digital
OUTPUTS	Single RCA line level output for connection to subwoofer
HEIGHT, WIDTH, DEPTH	39" (99.3cm), 7.8" (19.8cm), 13.5" (34.5cm)
WEIGHT	41.9lbs (19.02kg)
FINISH	Brushed Black Polymer Veneer
VOLTAGE	100V-120V / 220-240V selectable 50/60Hz internal power supply with region specific power cord
INCLUDED ACCESSORIES	<ul style="list-style-type: none"> • Remote Control (with 2 x AAA batteries) • Magnetic grille • 5M speaker wire with 4-wire connector • 1.8M power cord (region specific) • 2M 3.5mm aux cable • 3M Optical cable
BUILT FROM	2017

R26PF
 UVP / Paar
999,00 €



REFERENCE POWERED MONITORS

Klipsch
REFERENCE

R-15PM



TURNTABLE READY

BLUETOOTH®
WIRELESS TECHNOLOGY

PC READY



NO RECEIVER NEEDED



TV READY



SIMPLE SETUP



SPECIFICATIONS

FREQUENCY RESPONSE	62Hz - 24kHz +/- 3dB
LOW FREQUENCY EXTENSION	54Hz
CROSSOVER FREQUENCY	1800Hz
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix Horn
LOW FREQUENCY DRIVER	5.25" (13.3cm), copper spun magnetically shielded IMG woofer
AMPLIFIER POWER	50 Watts per channel
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via rear-firing port
INPUTS	<ul style="list-style-type: none"> • 1 x pair of RCA phono level inputs with switch for Phono/Line input versatility (Phono Preamp with ground screw terminal) • 1 x USB digital audio from a PC or Mac single RCA line level output for connection to sub. • 1 x Digital optical • 1 x 3.5mm mini jack line level • Bluetooth® wireless technology
HEIGHT	12.5" (31.8cm)
WIDTH	7" (17.8cm)
DEPTH	8.11" (20.6 cm)
WEIGHT	10.3 lbs (4.67kg)
FINISH	Brushed Black Polymer Veneer
BUILT FROM	2016

POWER PLAYER - SOUND THAT PACKS A PUNCH

The R-15PM powered monitors deliver room-filling sound without taking up much space. This highly efficient, powerful yet minimalist speaker engulfs listeners in their favorite movies and music.

DESIGNED FOR SIMPLE SET UP WITH YOUR TURNTABLE, TELEVISION, COMPUTER OR WIRELESS DEVICE

With an integrated phono pre-amp, Bluetooth® wireless technology, digital optical, analog RCA and USB inputs, your R-15PM is the best performing, most versatile monitor on the planet.

HIGH EFFICIENCY AMPLIFICATION

Forget the expense, clutter and hassle of an external A/V receiver. The R-15PM monitors incorporate individual ultra-low noise amplifiers custom designed to maximize system performance and eliminate the need for external amplification.

FULL FEATURED IR REMOTE

Allows easy access to system features such as dedicated source selection, track controls, and play/pause.

SYSTEM EXPANDABILITY

Seamlessly add a subwoofer to enhance low frequencies even further.

R15PM
 UVP / Paar
499,00 €



REFERENCE POWERED MONITORS

Klipsch
REFERENCE

R-14PM



TURNTABLE READY

BLUETOOTH®
WIRELESS TECHNOLOGY

PC READY



NO RECEIVER NEEDED



TV READY



SIMPLE SETUP

**NO RECEIVER NEEDED**

The Klipsch R-14PM internal amplifier eliminates the need for an expensive, complicated, external receiver.

REFERENCE ACOUSTICS

High Efficiency/Low Distortion, Wide Dynamic Range, Flat Frequency Response and Controlled Directivity are Klipsch's acoustic principles. These speakers embrace those ideals to deliver all the power, detail and emotion you would expect from a Klipsch Reference loudspeaker, no bullshit.

SIMPLE SETUP

With a wide range of digital, analog and wireless inputs, the R-14PM allows you to hook up any audio source quickly and easily.

USB DIGITAL AUDIO

Hook up your desktop or laptop computer with the included USB cable and play digital music files up to 24-bit / 96kHz sample rates.

TURNTABLE READY

The built-in phono pre-amp lets you enjoy your favorite records without the need for additional electronics. Simply hook up your turntable and listen.

BLUETOOTH® WIRELESS TECHNOLOGY

Works great with all Bluetooth-enabled smartphones, tablets and computers allowing you to play music directly from your device.

HIGH EFFICIENCY AMPLIFICATION

The R-14PM monitors incorporate individual ultra low-noise amplifiers custom-designed to maximize system performance.

SUBWOOFER OUTPUT

Want more bass? Use the subwoofer output to connect any powered subwoofer.

REMOTE CONTROL

An easy-to-use wireless remote control included.

SPECIFICATIONS

SYSTEM DESCRIPTION	Powered Monitor (pair)
FREQUENCY RESPONSE	80Hz - 20kHz
MAX OUTPUT	103dB @ 1M
TOTAL SYSTEM POWER	70W Total System Power (140W Peak) 35W per channel cont. @ <1% THD
HIGH FREQUENCY DRIVER	3/4" (1.9cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	4" (10.2cm) copper spun magnetically shielded IMG woofer
CROSSOVER FREQUENCY	2000 Hz (Passive)
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via rear-firing port
INPUTS	<ul style="list-style-type: none"> • Bluetooth® wireless technology • Phono/Line analog (with switch and ground screw terminal) • 3.5mm analog mini jack • USB digital • Optical digital
OUTPUTS	Single RCA line level output for connection to subwoofer
HEIGHT, WIDTH, DEPTH	9.75" (24.8cm), 5.88" (14.9cm), 7.5" (19.1cm)
WEIGHT	7.1lbs (3.2kg)
FINISH	Brushed black polymer veneer
VOLTAGE	100V-240V 50/60Hz internal power supply with region specific power cords
INCLUDED ACCESSORIES	<ul style="list-style-type: none"> • Remote control (with 2 x AAA batteries) • 4M speaker wire with soldered tips • 2M power cord (region specific) • 1.5M USB Type A to Type B cable • Rubber feet
BUILT FROM	2017

R14PM
 UVP / Paar
399,00 €