

		PA 16 MK2	PA 8 MK2 ULTRA	
Main Features				
Control	Power status (Button ON/OFF)	✓	✓	
	Power indication (LED, red / green)	✓	✓	
Protection	Overheat	✓	✓	
(Blinking LED)	Overcurrent	✓	✓	
(Similary 223)	Overvoltage	✓	✓	
	DC error	✓	✓	
Power up	Trigger control or front button	✓	✓	
Electronically controlled ventilation	Using several thermal sensors	✓	✓	
·	ű	·		
onnectivity	VI D	,	,	
Analog inputs	XLR RCA	√ N/A	√ N/A	
	Connected to network (DHCP or static IP)		IN/A ✓	
Ethernet	· · · · · ·	√ √		
Trigger in, trigger out	(daisy chain with electronic delay)	V	✓	
emote Monitoring via ISP processor User Interface				
	Serial number (settable, at production)	√ ,	√ ,	
	IP address Amplifier model	√ √	√	
	Temperature	√	· /	
	Fan speed	√	, ,	
	Power status and control	√	, ,	
	Mute status	✓	✓	
	Protection / malfunction	✓	✓	
pecifications				
Amplifier class	Pascal Audio	Class D	Class D	
Channel configuration		SE - 16	SE - 8 (Normal)	BTL - 4 (Bridged)
Chaimer configuration	RMS 8 Ω : 1 kHz 0.1% distortion	200 W	200 W	800 W
	RMS 8 Ω : 1 kHz 1% distortion	250 W	250 W	1000 W
Output power 2 channels driven				
2 Chames unven	RMS 4 Ω : 1 kHz 0.1% distortion	400 W	400 W	900 W
	RMS 4 Ω :1 kHz 1% distortion	490 W	490 W	1100 W
Output power	RMS 8 Ω: 20 Hz - 20 kHz 0.1% distortion	200 W	200 W	800 W
All channels driven	RMS 4 Ω: 20 Hz - 20 kHz 0.1% distortion	225 W	400 W	800 W
Frequency response	High: -3 dB CEM	50 kHz	50 kHz	50 kHz
	Low : -3 dB CEM	10 Hz	10 Hz	10 Hz
Signal / Noise ratio (Bandwidth: 20 kHz)	Referred to P-rated	> 115 dB	> 115 dB	> 115 dB
THD (20Hz-20kHz), 1 Watt to -1dB max. power		< 0,03%	< 0,03%	< 0,03%
Galn	Standard	26 dB	26 dB	32 dB
Damping factor		> 400 < 30 dB	> 400 < 30 dB	
Fan noise (max.)		< 30 UB	< 30 u	U
ower Supply	V-14	1001/1- 2401/	100V to 240V SWITCHING MODE 3200 W (Ultra high current) Universal	
	Voltage range	100V to 240V		
	Туре	SWITCHING MODE		
	Power supply capacity	3200 W		
	Range selection	Universal		
asing				
	Home / Rack	V / V	√ /√	
	Gross weight (kg)	25,00	25,00	
	Net weight (kg)	21,00	21,00	
	Size	3RU	21,00 3RU	
	Dimensions - product (cm) feet and connectors included	49 x 43,5 x 15	49 x 43,5 x 15	
	Dimensions - with box (cm)	67 x 63 x 30	67 x 63 x 30	
	(611)			

All trademarks are the property of their respective owners. The information and product specifications contained in this datasheet are subject to change at any time without notice. StormAudio accepts no liability or responsibility for any errors or omissions in the information on this datasheet or for damages resulting from relying on the content of this datasheet.